

Insulation Resistance Tester



Specifications

Basic Functions	Range	Best Accuracy
Output Voltage	250 V / 500 V / 1,000 V	±10%
Nominal Current	250 V / 500 V 1 mA 500 V / 1,000 V 1 mA 1,000 V / 2,500 V 1 mA	±10%
Short Circuit Current	< 2 mA	✓
Insulation Resistance Measurement	250 V: 3 MW to 2,000 MW 500 V: 3 MW to 2,000 MW 1,000 V: 3 MW to 2 GW	±3% + 5
Voltage Measurement	1,000 V dc 750 V ac	± (2% + 3)
Special Functions		
Auto Ranging	-	✓
Low Battery Display	-	
Alarm Light Display	-	
Display Backlight	-	
Alarm Buzzer	-	

General Characteristics

Power	1.5 V Alkaline Battery × 6
LCD Size	70.6 × 34 mm
Product Colour	Orange and Grey
Product Net Weight	500 g
Product Size	150 × 100 × 71 mm
Standard Accessories	Battery, Probe, Alligator Clip, Test Lead, English Manual, Carrying Bag, Gallus



Insulation Resistance Tester



General Characteristics

Standard Individual Packing	Gift Box
Standard Quantity per Carton	20 Pieces
Standard Carton Measurement	500 × 380 × 330 mm (0.063 CBM per Standard Carton)
Standard Carton Gross	10.5 kg

* Available at Extra Cost Specifications and other Information are Subject to Change without Further Notice

Part Number Table

Description	Part Number
Tester, Insulation, Resistance	72-9400

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA® is the registered trademark of the Group. © Premier Farnell plc 2011.

